



60 mil Non-Reinforced Membrane Data Sheet

Product Description:

N.R. Detail Flashing Rolls are non-reinforced PVC Single-Ply Membrane. They are available in 60 mil thick, 12”x 50’ rolls. N.R. Detail Flashing is a non-reinforced, flexible product that is used for detail work.

Application:

N.R. Detail Membrane can be heated slightly and stretched to conform around various shapes. Seams are heat welded together using standard hot air welding tools.

Colors:

Available in White, SR Tan, SR Grey, Tan, Brown, and Grey



LEED Information

Pre-consumer Recycled Content	10%
Post-consumer Recycled Content	0%
Manufacturing Location	Mountain Top, PA

Typical Properties and Characteristics

Properties	ASTM Test Method	Specification
Tolerance on nominal Thickness	ASTM D751	±8
Weight, lb/ft ² (kg/m ²), typical		0.44 lb/ft ²
Tensile strength, min., psi (Mpa)	ASTM D638	1500
Elongation, ultimate, min., %	ASTM D638	200/225 (MD/TD)
Tear strength, min., lbf/in (kN/m)	ASTM D1004	10
Heat aging: 28 days % Retention	ASTM D4434	90
Resistance to Xenon-arc weathering Xenon-Arc, 5040 kJ/m ² total radiant Exposure, visual condition at 7X	ASTM D4434	No cracking/crazing negligible discoloration