

Product Description:

Phoenix Products Pipe Flashings are hand welded 60mil reinforced upper welded to a 60mil reinforced base. They are manufactured in a controlled environment warehouse providing a top quality flashing, lasting much longer than traditional non-reinforced flashings. Our flashings are designed for a quick and effective install dramatically reducing labor costs. Please see sizing chart below for appropriate flashing.

Use: Phoenix Products Pipe Flashings designed for use in both split and non-split applications. Our flashings are used to waterproof a number of penetrations. Please contact your Technical Representative if you are unsure what flashing to use. They would be happy to take your call.

Colors: Available in White, SR Tan, SR Grey, Tan, Brown, and Grey

<u>Property</u>	<u>Test</u>	<u>Requirement</u>	<u>60 Mil</u>
Overall thickness of PVC sheet,	ASTM D751	0.054	0.060 nom
Breaking strength, min. (lbf/	ASTM D751	240	Pass
Elongation at the break, min. %	ASTM D751	20	Pass
Retention of properties after heat aging (min. % of original):	ASTM D4434	90	Pass
Tearing strength, min. (lbf	ASTM D751	45	Pass
Low temperature bend	ASTM D2136	-40°F	Pass
Accelerated weathering Cracking (7x magnification) Crazing (7x magnification)	ASTM D4434	None None	Pass
Dimension stability, max %	ASTM D1204	0.5	Pass
Change in weight after immersion in water, max %	ASTM D570	3.0	1.5 nom
Static puncture resistance	ASTM D5602	33	Pass
Dynamic puncture resistance	ASTM D5635	14.7	Pass

<u>Flashing type</u>	<u>Base Flashing</u>	<u>Base</u>	<u>Top</u>	<u>Height</u>	<u>Box Quantity</u>
Short A cone	14"	3-1/4"	1/4"	5-1/2"	25
A cone	15"	4-1/2"	1"	8-1/2"	25
B cone	15-1/2"	5-1/4"	2-3/8"	10-1/2"	25
C cone	17-1/2"	8"	4"	10-1/2"	10
D cone	23"	12"	7-1/2"	9"	10
E cone	28"	18"	9-1/2"	12"	10
4" Oval 0.25 Cone	22"	6"x10"	3"x6"	5"	25

